

EXTERIOR VENUE SERIES



Camlock Load Centers

	Model No:	EV1200-1X400
	Description	400a Camlock Load Ctr. (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 400a / 1200a
	Input Type	3-phase 400a 208Y-/120v 5wire Camlock Type
	Output Type	2 - 400a 208Y-/120v 5wire Camlock (duplexed) 4 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	1 - 400a 240v Circuit Breaker (65K AIC) Adjustable Protection 2 - 20amp 120v Circuit Breakers (10K AIC) w/ GFCI
	Dims & Weight (Std. Frame) w/ Rolling Truck Pack Frame	22"L x 14"W x 29"H - 68lbs. 22.5"L x 18"W x 32"H - 88lbs.
	Model No:	EV1200-2X225
	Description	225a Camlock Load Ctr. (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 400a / 1200a
	Input Type - Flow Thru	3-phase 400a 208Y-/120v 5wire Camlock Type
	Output Type	2 - 225a 208Y-/120v 5wire Camlock 4 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	2 - 225a 240v Circuit Breakers (65K AIC) 2 - 20amp 120v Circuit Breakers (10K AIC) w/ GFCI
	Dimensions & Weight w/ Rolling Truck Pack Frame	22"L x 14"W x 29"H - 85lbs. 22.5"L x 18"W x 32"H - 108lbs.
	Model No:	EV1200-3X150
	Description	150a Camlock Load Ctr. (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 400a / 1200a
	Input Type - Flow Thru	3-phase 400a 208Y-/120v 5wire Camlock Type
	Output Type	3 - 150a 208Y-/120v 5wire Camlock 4 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	3 - 240v 150a Circuit Breakers (65K AIC) 2 - 20amp 120v Circuit Breakers (10K AIC) w/ GFCI
	Dimensions & Weight w/ Rolling Truck Pack Frame	22"L x 14"W x 29"H - 95lbs. 22.5"L x 18"W x 32"H - 115lbs.
	Model No:	EV1200-L2130
	Description	Camlock to L2130 Twistlock Distribution Ctr. (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 360a / 1080a
	Input Type - Flow Thru	3-phase 400a 208Y-/120v 5wire Camlock Type
	Output Type	12 - 30a 208Y-/120v (L2130) Twistlock Receptacles 4 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	12 - 30a 3pole Circuit Breaker (10K AIC) 2 - 20amp 120v Circuit Breakers (10K AIC) w/ GFCI
	Dimensions & Weight w/ Rolling Truck Pack Frame	22"L x 14"W x 29"H - 69lbs. 22.5"L x 18"W x 32"H - 89lbs.
	Model No:	EV1200-L2120
	Description	Camlock to L2120 Twistlock Distribution Ctr. (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 240a / 720a
	Input Type - Flow Thru	3-phase 400a 208Y-/120v 5wire Camlock Type
	Output Type	12 - 20a 208Y-/120v (L2120) Twistlock Receptacles 4 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	12 - 20a 3pole Circuit Breaker (10K AIC) 2 - 20amp 120v Circuit Breakers (10K AIC) w/ GFCI
	Dimensions & Weight w/ Rolling Truck Pack Frame	22"L x 14"W x 29"H - 68lbs. 22.5"L x 18"W x 32"H - 88lbs.

Specifications subject to change.

LIT-EV-CLC-090104 © AC Power Distribution, Inc.



AC Power Distribution, Inc. The Entertainment Industry's Power Solution!



3060 N. California St. - Burbank, CA 91504
 Tel: 818-848-4004 Fax: 818-848-4441 Toll Free: 877-55-ACPWR
www.acpowerdistribution.com