

# EXTERIOR VENUE SERIES



## Mini-Cam Distribution Systems

	<b>Model No:</b>	<b>EV1200</b>
	Description	Camlock to Mini-Cam Distribution Ctr. (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 400a / 1200a
	Input Type - Flow Thru	3-phase 400a 208Y-/120v 5wire Camlock Type
	Output Type	4 - 100a 208Y-/120v 5wire Mini-Cam 4 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	4 - 100a 3pole Circuit Breakers (10K AIC) 2 - 20amp 120v Circuit Breakers (10K AIC) w/ GFCI
	Dims & Weight (Std. Frame) w/ Rolling Truck Pack Frame	22"L x 14"W x 29"H - 75lbs. 22.5"L x 18"W x 32"H - 95lbs.
	<b>Model No:</b>	<b>EV300-L2130</b>
	Description	Mini-Cam to L2130 Twistlock Distro (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 100a / 300a
	Input Type	100a 208Y-/120v 5wire Mini-Cam Type
	Output Type	4 - 30a 120/208v (L2130) Twistlock Receptacles 2 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	4 - 30a 3pole Circuit Breakers (10K AIC) 1 - 20amp 120v Circuit Breaker (10K AIC) w/ GFCI
	Dimensions & Weight	17"L x 12"W x 20"H - 27lbs.
	<b>Model No:</b>	<b>EV300-L2120</b>
	Description	Mini-Cam to L2120 Twistlock Distro (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 100a / 300a
	Input Type	100a 208Y-/120v 5wire Mini-Cam Type
	Output Type	5 - 20a 120/208v (L2120) Twistlock Receptacles 2 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	5 - 20a 3pole Circuit Breakers (10K AIC) 1 - 20amp 120v Circuit Breaker (10K AIC) w/ GFCI
	Dimensions & Weight	17"L x 12"W x 20"H - 29lbs.
	<b>Model No:</b>	<b>EV300-50</b>
	Description	Mini-Cam to 50a 125/250v Twistlock Distro (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 100a / 300a
	Input Type	100a 208Y-/120v 5wire Mini-Cam Type
	Output Type	3 - 50a 125/250v Twistlock Receptacles 2 - 20amp Courtesy Outlets - GFCI Protected
	Circuit Protection	4 - 30a 3pole Circuit Breakers (10K AIC) 1 - 20amp 120v Circuit Breaker (10K AIC) w/ GFCI
	Dimensions & Weight	17"L x 12"W x 20"H - 26lbs.
	<b>Model No:</b>	<b>EV300-E</b>
	Description	Mini-Cam to Edison (GFCI) Distro (NEMA 3R)
	Phase & Amperage (line/total)	3- phase 80a / 240a
	Input Type	100a 208Y-/120v 5wire Mini-Cam Type
	Output Type	12 - 20a 120v Edison Receptacles GFCI Protected
	Circuit Protection	12 - 20a 120v Circuit Breakers (10K AIC) w/ GFCI
	Dimensions & Weight	17"L x 12"W x 20"H - 29lbs.

Specifications subject to change.

LIT-EV-MCD-090104 © AC Power Distribution, Inc.



**AC Power Distribution, Inc.....The Entertainment Industry's Power Solution!**



3060 N. California St. - Burbank, CA 91504  
 Tel: 818-848-4004 Fax: 818-848-4441 Toll Free: 877-55-ACPWR  
[www.acpowerdistribution.com](http://www.acpowerdistribution.com)